



Rapid installation and fully power-independent, this high-spec Video-Verified Alarm system will detect movement via multiple sensors and send a short video clip via the mobile network to any location

Specifications: inView Video Verified

Indoor and outdoor PIR camera sensors with day/night visibility, and completely wire-free. Battery life for all devices and control panel is up to 4 years

| Technical Information | |
|-------------------------|--|
| Dimensions | 130mm x 102mm x 141mm (approx.) |
| Material | Polycarbonate UL94 |
| Power requirements | Battery type C Lithium batteries 3.6v LS14500 |
| Radio type | Spread spectrum bidirectional |
| Radio frequency | 868MHz |
| Transmission security | AES encryption algorithm |
| Alerts | Radio, batteries, tamper, position |
| Radio antenna | Integrated |
| Operating temperature | External: -20C to +60C / Internal: -10C to +55C |
| Mounting height | 2m to 4m (approx.) |
| Mounting angle | 5° to 10° (external) |
| Camera view angle | External: 110° / Internal: 90° |
| Detection range: | External: 18m / Internal: 12m (at 2m mount height) |
| Sensor type | CMOS |
| Daylight video | Programmable: colour or black & white |
| Night video | Automatic black & white infrared |
| Infrared illumination | External: up to 12m / Internal: up to 7m |
| Video format | MJPEG-WMV, MJPEG-DIFF |
| Video frame rate | 5 images per second |
| Video duration | Programmable (10 seconds by default) |
| Video resolution | QVGA (320x240) |
| Video quality | SQ or HQ |
| Average video file size | 220K |
| Image format | JPEG |
| Image resolution | VGA (640px x 480px) |
| Image quality | HQ or SQ |
| Average image file size | 8 Kb |
| Approvals | External: CE NF EN50131-2-2 |
| | Internal: CE / EN50131 / NF&A2P |



External camera sensor



Internal camera sensor

To find out how we can help you

Call: 0141 611 7812 or visit www.clearwayscotland.co.uk

